

Mini point and line emitter - Series LT1



M1301H2VL0

Type of projection: Line
Wavelength: 635 nm (bright red)
Max output power: 1 mW
Supply voltage: 5-30 Vdc
Protection class: IP64

TECHNICAL DETAILS

Code	M1301H2VL0
Light source	Laser diode
Type of projection	Line
Wavelength	635 nm (bright red)
Max output power	1 mW
Supply voltage	5-30 Vdc
Operating current	<40 mA
Connection	Cable 2x0,25 cm 200
Casing	Green anod.alum.
Dimension	11X65 mm
Linelength	Max 1,5mt
Protection class	IP64
Laser class	2
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +122 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Bright red
Note	The visibility and the length of the line depend on the mounting of the laser and the brightness of the environment. For better use you have to specify the focus distance. If not specified, emitter is focused for infinity. The lens has a spread of 90°. The line has a wide of mm 1800 at a distance of mm 1000 from the emission point, perpendicularly to laser beam. Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 11 mm diam module, black

LASERTECH®

— industrial laser pointers —