

Versatile point, cross, line, circle emitter, panel mount - Series LT1M



M2310A2V00

Type of projection: Dot
Wavelength: 635 nm (bright red)
Max output power: 10 mW
Supply voltage: 5 Vdc
Protection class: IP64

TECHNICAL DETAILS

| | |
|------------------------------------|--|
| Code | M2310A2V00 |
| Light source | Laser diode |
| Type of projection | Dot |
| Wavelength | 635 nm (bright red) |
| Max output power | 10 mW |
| Supply voltage | 5 Vdc |
| Operating current | <70 mA |
| Connection | Cable 2x0,25 cm 200 |
| Casing | Green anod.alum. |
| Dimension | 14x55 mm |
| Protection class | IP64 |
| Laser class | 3B |
| Storage temperature °C/°F | -40 +85 °C / -40 +185 °F |
| Operating temperature °C/°F | -10 +50 °C / 14 +122 °F |
| Application sector | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc. |
| Color | Bright red |
| Note | Two rings are included in the price. For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000..Other optical projections available on request |

RELATED ACCESSORIES

- Stabilized power supplier, input 80-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Flexible support, M14x1 threaded , 180 mm lenght, black
- Flexible support, M14x1 threaded , 280 mm lenght, black

LASERTECH®

— industrial laser pointers —