

Versatile point, cross, line, circle emitter, panel mount - Series LT1M



M2503A2VL0

Type of projection: Line Wavelength: 650 nm (red) Max output power: 3 mW Supply voltage: 5 Vdc Protection class: IP64

TECHNICAL DETAILS

Code M2503A2VL0 **Light source** Laser diode

Type of projection Line

Wavelength 650 nm (red) 3 mW Max output power

Supply voltage 5 Vdc **Operating current** <40 mA

Connection Cable 2x0,25 cm 200 Casing Green anod.alum. **Dimension** 14x65 mm

Linelength Max 1,5mt **Protection class** IP64

Laser class 2M

Storage temperature °C/°F -40 +85 °C / -40 +185 °F

Operating temperature °C/°F -10 +50 °C / 14 +140 °F

Application sector Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.

Color Red

> Two rings are included in the price. For better use you have to specify the focus distance. If not specified, emitter is focused for infinity. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70; 20° spread = mm 310; 30° spread = mm 660; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the length of the line depend on the mounting of the laser and the brightness of the environment. Other optical projections available on request

RELATED ACCESSORIES

Note

- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Flexible support, M14x1 threaded , 180 mm lenght, black
- Flexible support, M14x1 threaded, 280 mm lenght, black

