

Versatile point, cross, line, circle emitter - Series LT1S



M3303A2VC0

Type of projection: Circle
Wavelength: 635 nm (bright red)
Max output power: 3 mW
Supply voltage: 5 Vdc
Protection class: IP64

TECHNICAL DETAILS

Code	M3303A2VC0
Light source	Laser diode
Type of projection	Circle
Wavelength	635 nm (bright red)
Max output power	3 mW
Supply voltage	5 Vdc
Operating current	<40 mA
Connection	Cable 2x0,25 cm 200
Casing	Green anod.alum.
Dimension	14x65 mm
Protection class	IP64
Laser class	2M
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +122 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Bright red
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. The circle (spread 3°) has a central dot and a diameter of mm 40 at a distance of mm 1000 from the emission point. Circle lenses with spread 3°, 4°, 34°, 45° available. .Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 14 mm diam module, black
- Ball-shaped head bracket for 14 mm diam module, black
- Reduction bush for 14 mm diam module, black

LASERTECH®

— industrial laser pointers —