

Versatile point, cross, line, circle emitter - Series LT1S



M3701A2VX0

Type of projection: Cross
Wavelength: 670 nm (dark red)
Max output power: 1 mW
Supply voltage: 5 Vdc
Protection class: IP64

TECHNICAL DETAILS

Code	M3701A2VX0
Light source	Laser diode
Type of projection	Cross
Wavelength	670 nm (dark red)
Max output power	1 mW
Supply voltage	5 Vdc
Operating current	<50 mA
Connection	Cable 2x0,25 cm 200
Casing	Green anod.alum.
Dimension	14x65 mm
Protection class	IP64
Laser class	2
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +140 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Dark red
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. The cross (spread 10°) has a total wide of mm 160 at a distance of mm 1000 from the emission point, perpendicularly to laser beam. Cross lenses with spread 2°, 5°, 10°, 25°, 30°, 45°, 75° available. .Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 14 mm diam module, black
- Ball-shaped head bracket for 14 mm diam module, black
- Reduction bush for 14 mm diam module, black

LASERTECH®

— industrial laser pointers —