

## Versatile point, cross, line, circle emitter - Series LT1S



### M3701H2VC0

**Type of projection:** Circle  
**Wavelength:** 670 nm (dark red)  
**Max output power:** 1 mW  
**Supply voltage:** 5-30 Vdc  
**Protection class:** IP64

## TECHNICAL DETAILS

|                                    |   |
|------------------------------------|---|
| <b>Code</b>                        | M3701H2VC0  |
| <b>Light source</b>                | Laser diode   |
| <b>Type of projection</b>          | Circle  |
| <b>Wavelength</b>                  | 670 nm (dark red)   |
| <b>Max output power</b>            | 1 mW  |
| <b>Supply voltage</b>              | 5-30 Vdc  |
| <b>Operating current</b>           | <50 mA  |
| <b>Connection</b>                  | Cable 2x0,25 cm 200   |
| <b>Casing</b>                      | Green anod.alum.  |
| <b>Dimension</b>                   | 14x65 mm  |
| <b>Protection class</b>            | IP64  |
| <b>Laser class</b>                 | 2   |
| <b>Storage temperature °C/°F</b>   | -40 +85 °C / -40 +185 °F  |
| <b>Operating temperature °C/°F</b> | -10 +50 °C / 14 +140 °F   |
| <b>Application sector</b>          | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.  |
| <b>Color</b>                       | Dark red  |
| <b>Note</b>                        | For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. The circle (spread 3°) has a central dot and a diameter of mm 40 at a distance of mm 1000 from the emission point. Circle lenses with spread 3°, 4°, 34°, 45° available. .Other optical projections available on request |

## RELATED ACCESSORIES

- Stabilized power supplier, input 80-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 14 mm diam module, black
- Ball-shaped head bracket for 14 mm diam module, black
- Reduction bush for 14 mm diam module, black

# LASERTECH®

— industrial laser pointers —