

Versatile point, cross, line, circle emitter - Series LT1S



M3701H2VL0

Type of projection: Line Wavelength: 670 nm (dark red) Max output power: 1 mW Supply voltage: 5-30 Vdc Protection class: IP64

TECHNICAL DETAILS

Code M3701H2VL0
Light source Laser diode

Type of projection Line

Wavelength 670 nm (dark red)

Max output power1 mWSupply voltage5-30 VdcOperating current<50 mA</th>

ConnectionCable 2x0,25 cm 200CasingGreen anod.alum.Dimension14x65 mmLinelengthMax 1mt

Protection class IP64 Laser class 2

Storage temperature °C/°F -40 +85 °C / -40 +185 °F

Operating temperature °C/°F -10 +50 °C / 14 +140 °F

Operating temperature °C/°F -10 +50 °C / 14 +140 °F

Application sectorNautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.

Color Dark red

For better use you have to specify the focus distance. If not specified, emitter is focused for infinity. Line lenses with spread 5° , 20° , 30° , 45° , 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70; 20° spread = mm 310; 30° spread = mm 660; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the length of the line depend on the mounting of the laser and the brightness of the environment. Other optical projections available on request

RELATED ACCESSORIES

Note

- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 14 mm diam module. black
- Ball-shaped head bracket for 14 mm diam module, black
- Reduction bush for 14 mm diam module, black

