— industrial laser pointers —

**LASERTECH**<sup>®</sup>

## Versatile point, cross, line, circle emitter - Series LT1S



## M3705H2VL0

Type of projection: Line Wavelength: 670 nm (dark red) Max output power: 5 mW Supply voltage: 5-30 Vdc Protection class: IP64

## **TECHNICAL DETAILS**

| Code                        | M3705H2VL0   |
|-----------------------------|--|
| Light source                | Laser diode  |
| Type of projection          | Line   |
| Wavelength                  | 670 nm (dark red)  |
| Max output power            | 5 mW   |
| Supply voltage              | 5-30 Vdc   |
| Operating current           | <65 mA   |
| Connection                  | Cable 2x0,25 cm 200  |
| Casing                      | Green anod.alum.   |
| Dimension                   | 14x65 mm   |
| Linelength                  | Max 1,5mt  |
| Protection class            | IP64   |
| Laser class                 | 2M   |
| Storage temperature °C/°F   | -40 +85 °C / -40 +185 °F   |
| Operating temperature °C/°F | -10 +50 °C / 14 +140 °F  |
| Application sector          | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.   |
| Color                       | Dark red   |
| Note                        | For better use you have to specify the focus distance. If not specified, emitter is focused for infinity. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it |

infinity. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows:  $05^{\circ}$  spread = mm 70 ; 20° spread = mm 310 ; 30° spread = mm 660 ; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment. Other optical projections available on request

## **RELATED ACCESSORIES**

- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 14 mm diam module, black
- Ball-shaped head bracket for 14 mm diam module, black
- Reduction bush for 14 mm diam module, black

