

Compact and powerful red light emitter for marking cutting lines and many other optical projections - Series LT1S20



M4303A2VL0

Type of projection: Line
Wavelength: 635 nm (bright red)
Max output power: 3 mW
Supply voltage: 5 Vdc
Protection class: IP67

TECHNICAL DETAILS

Code	M4303A2VL0
Light source	Laser diode
Type of projection	Line
Wavelength	635 nm (bright red)
Max output power	3 mW
Supply voltage	5 Vdc
Operating current	<40 mA
Connection	Cable 2x0,25 cm 200
Casing	Green anod.alum.
Dimension	20x130 mm
Linelength	Max 2mt
Protection class	IP67
Laser class	2M
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +122 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Bright red
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for infinity. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70 ; 20° spread = mm 310 ; 30° spread = mm 660 ; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment. Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier, input 80-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Dimming flap 20 mm diam, black
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included

LASERTECH®

— industrial laser pointers —

- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —