

Compact and powerful red light adjustable emitter for points, crosses, circles and marker lines - Series LT1S20 - ADJUSTABLE FOCUS



M4320L4V00R

Type of projection: Dot
Wavelength: 635 nm (bright red)
Max output power: 20 mW
Supply voltage: 9-36 Vdc 10-30 Vac Trigger 5-30Vdc
Protection class: IP67

TECHNICAL DETAILS

| | |
|------------------------------------|--|
| Code | M4320L4V00R |
| Light source | Laser diode |
| Type of projection | Dot |
| Wavelength | 635 nm (bright red) |
| Max output power | 20 mW |
| Supply voltage | 9-36 Vdc 10-30 Vac Trigger 5-30Vdc |
| Operating current | <80 mA |
| Connection | M12 connector + cm 500 cable |
| Casing | Green anod.alum. |
| Dimension | 20x135 mm |
| Protection class | IP67 |
| Laser class | 3B |
| Storage temperature °C/°F | -40 +85 °C / -40 +185 °F |
| Operating temperature °C/°F | -10 +50 °C / 14 +122 °F |
| Application sector | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc. |
| Color | Bright red |
| Note | Focal length and the projected figure thickness are manually adjustable with the steel ring from ? 50mm to 20mt .Other optical projections available on request |

RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —