

Compact and powerful red light adjustable emitter for points, crosses, circles and marker lines - Series LT1S20 - ADJUSTABLE FOCUS



M4320L4VL0R

Type of projection: Line
Wavelength: 635 nm (bright red)
Max output power: 20 mW
Supply voltage: 9-36 Vdc 10-30 Vac Trigger 5-30Vdc
Protection class: IP67

TECHNICAL DETAILS

Code	M4320L4VL0R
Light source	Laser diode
Type of projection	Line
Wavelength	635 nm (bright red)
Max output power	20 mW
Supply voltage	9-36 Vdc 10-30 Vac Trigger 5-30Vdc
Operating current	<80 mA
Connection	M12 connector + cm 500 cable
Casing	Green anod.alum.
Dimension	20x135 mm
Linelength	Max 7mt
Protection class	IP67
Laser class	2M
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +122 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Bright red
Note	Focal length and the projected figure thickness are manually adjustable with the steel ring from ? 50mm to 20mt. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70 ; 20° spread = mm 310 ; 30° spread = mm 660 ; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the length of the line depend on the mounting of the laser and the brightness of the environment. Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —