

## Compact and powerful red light adjustable emitter for points, crosses, circles and marker lines - Series LT1S20 - ADJUSTABLE FOCUS



### M4340L4VL0R

**Type of projection:** Line

**Wavelength:** 635 nm (bright red)

**Max output power:** 40 mW

**Supply voltage:** 9-36 Vdc 10-30 Vac Trigger 5-30Vdc

**Protection class:** IP67

## TECHNICAL DETAILS

Code	M4340L4VL0R
Light source	Laser diode
Type of projection	Line
Wavelength	635 nm (bright red)
Max output power	40 mW
Supply voltage	9-36 Vdc 10-30 Vac Trigger 5-30Vdc
Operating current	<110 mA
Connection	M12 connector + cm 500 cable
Casing	Green anod.alum.
Dimension	20x135 mm
Linelength	Max 10mt
Protection class	IP67
Laser class	3B
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +122 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Bright red
Note	Focal lenght and the projected figure thickness are manually adjustable with the steel ring from ? 50mm to 20mt. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70 ; 20° spread = mm 310 ; 30° spread = mm 660 ; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment. Other optical projections available on request

## RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

# LASERTECH®

— industrial laser pointers —