

Compact and powerful red light emitter for marking cutting lines and many other optical projections - Series LT1S20



M4505B4VL0

Type of projection: Line
Wavelength: 650 nm (red)
Max output power: 5 mW
Supply voltage: 9-36 Vdc 10-30 Vac
Protection class: IP67

TECHNICAL DETAILS

| | |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code | M4505B4VL0 |
| Light source | Laser diode |
| Type of projection | Line |
| Wavelength | 650 nm (red) |
| Max output power | 5 mW |
| Supply voltage | 9-36 Vdc 10-30 Vac |
| Operating current | <30 mA |
| Connection | M12 connector + cm 500 cable |
| Casing | Green anod.alum. |
| Dimension | 20x145 mm |
| Linelength | Max 2mt |
| Protection class | IP67 |
| Laser class | 2M |
| Storage temperature °C/°F | -40 +85 °C / -40 +185 °F |
| Operating temperature °C/°F | -10 +50 °C / 14 +140 °F |
| Application sector | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc. |
| Color | Red |
| Note | For better use you have to specify the focus distance. If not specified, emitter is focused for infinity. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70 ; 20° spread = mm 310 ; 30° spread = mm 660 ; 45° spread = 800mm; 90° spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a 90° spread lens. The visibility and the length of the line depend on the mounting of the laser and the brightness of the environment. Other optical projections available on request |

RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vac, output 24Vdc, 1,25A, 2 poles 10A plug
- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Dimming flap 20 mm diam, black
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —