

## Compact and powerful red light adjustable emitter for points, crosses, circles and marker lines - Series LT1S20 - ADJUSTABLE FOCUS



### M4650L4V00R

**Type of projection:** Dot  
**Wavelength:** 660 nm (red)  
**Max output power:** 50 mW  
**Supply voltage:** 9-36 Vdc 10-30 Vac Trigger 5-30Vdc  
**Protection class:** IP67

## TECHNICAL DETAILS

<b>Code</b>	M4650L4V00R
<b>Light source</b>	Laser diode
<b>Type of projection</b>	Dot
<b>Wavelength</b>	660 nm (red)
<b>Max output power</b>	50 mW
<b>Supply voltage</b>	9-36 Vdc 10-30 Vac Trigger 5-30Vdc
<b>Operating current</b>	<60 mA
<b>Connection</b>	M12 connector + cm 500 cable
<b>Casing</b>	Green anod.alum.
<b>Dimension</b>	20x135 mm
<b>Protection class</b>	IP67
<b>Laser class</b>	3B
<b>Storage temperature °C/°F</b>	-40 +85 °C / -40 +185 °F
<b>Operating temperature °C/°F</b>	-10 +75 °C / 14 +167 °F
<b>Application sector</b>	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
<b>Color</b>	Red
<b>Note</b>	Focal length and the projected figure thickness are manually adjustable with the steel ring from ? 50mm to 20mt .Other optical projections available on request

## RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

# LASERTECH®

— industrial laser pointers —