

Compact and powerful red light emitter for marking cutting lines and many other optical projections - Series LT1S20



M4680L4V00

Type of projection: Dot
Wavelength: 660 nm (red)
Max output power: 80 mW
Supply voltage: 9-36 Vdc 10-30 Vac Trigger 5-30Vdc
Protection class: IP67

TECHNICAL DETAILS

Code	M4680L4V00
Light source	Laser diode
Type of projection	Dot
Wavelength	660 nm (red)
Max output power	80 mW
Supply voltage	9-36 Vdc 10-30 Vac Trigger 5-30Vdc
Operating current	<70 mA
Connection	M12 connector + cm 500 cable
Casing	Green anod.alum.
Dimension	20x145 mm
Protection class	IP67
Laser class	3B
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +75 °C / 14 +167 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Red
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000 .Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —