

## Compact and powerful red light emitter for marking cutting lines and many other optical projections - Series LT1S20



### M4705B4VC0

**Type of projection:** Circle  
**Wavelength:** 670 nm (dark red)  
**Max output power:** 5 mW  
**Supply voltage:** 9-36 Vdc 10-30 Vac  
**Protection class:** IP67

## TECHNICAL DETAILS

|                                    |   |
|------------------------------------|---|
| <b>Code</b>                        | M4705B4VC0  |
| <b>Light source</b>                | Laser diode   |
| <b>Type of projection</b>          | Circle  |
| <b>Wavelength</b>                  | 670 nm (dark red)   |
| <b>Max output power</b>            | 5 mW  |
| <b>Supply voltage</b>              | 9-36 Vdc 10-30 Vac  |
| <b>Operating current</b>           | <40 mA  |
| <b>Connection</b>                  | M12 connector + cm 500 cable  |
| <b>Casing</b>                      | Green anod.alum.  |
| <b>Dimension</b>                   | 20x145 mm   |
| <b>Protection class</b>            | IP67  |
| <b>Laser class</b>                 | 2M  |
| <b>Storage temperature °C/°F</b>   | -40 +85 °C / -40 +185 °F  |
| <b>Operating temperature °C/°F</b> | -10 +50 °C / 14 +140 °F   |
| <b>Application sector</b>          | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.  |
| <b>Color</b>                       | Dark red  |
| <b>Note</b>                        | For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. The circle (spread 3°) has a central dot and a diameter of mm 40 at a distance of mm 1000 from the emission point. Circle lenses with spread 3°, 4°, 34°, 45° available. .Other optical projections available on request |

## RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vac, output 24Vdc, 1,25A, 2 poles 10A plug
- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

# LASERTECH®

— industrial laser pointers —