

Compact large cross emitter - Series LT1S20CR



M5501A4VX0

Type of projection: Cross
Wavelength: 650 nm (red)
Max output power: 1 mW
Supply voltage: 5 Vdc
Protection class: IP64

TECHNICAL DETAILS

| | |
|------------------------------------|---|
| Code | M5501A4VX0 |
| Light source | Laser diode |
| Type of projection | Cross |
| Wavelength | 650 nm (red) |
| Max output power | 1 mW |
| Supply voltage | 5 Vdc |
| Operating current | <60mW |
| Connection | M12 connector + cm 500 cable |
| Casing | Green anod.alum. |
| Dimension | 20/30x125 mm |
| Protection class | IP64 |
| Laser class | 2 |
| Storage temperature °C/°F | -40 +85 °C / -40 +185 °F |
| Operating temperature °C/°F | -10 +50 °C / 14 +140 °F |
| Application sector | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc. |
| Color | Red |
| Note | For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. The cross has a total wide of mm 1800 at a distance of mm 1000 from the emission point, perpendicularly to laser beam. |

RELATED ACCESSORIES

- Stabilized power supplier, input 80-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —