

Versatile point, cross, line, circle emitter with M8 connector - Series LT2S



N3703HBV00

Type of projection: Dot
Wavelength: 670 nm (dark red)
Max output power: 3 mW
Supply voltage: 5-30 Vdc
Protection class: IP64

TECHNICAL DETAILS

Code	N3703HBV00
Light source	Laser diode
Type of projection	Dot
Wavelength	670 nm (dark red)
Max output power	3 mW
Supply voltage	5-30 Vdc
Operating current	<60 mA
Connection	M8 connector + cm 300 cable
Casing	Green anod.alum.
Dimension	14X85 mm
Protection class	IP64
Laser class	3R
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +140 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Dark red
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000 .Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier, input 80-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 14 mm diam module, black
- Ball-shaped head bracket for 14 mm diam module, black
- Reduction bush for 14 mm diam module, black

LASERTECH®

— industrial laser pointers —