

## Versatile point, cross, line, circle emitter with M8 connector - Series LT2S



## N3705HBVL0

Type of projection: Line Wavelength: 670 nm (dark red) Max output power: 5 mW Supply voltage: 5-30 Vdc Protection class: IP64

## **TECHNICAL DETAILS**

Code	N3705HBVL0
Light source	Laser diode
Type of projection	Line
Wavelength	670 nm (dark red)
Max output power	5 mW
Supply voltage	5-30 Vdc
Operating current	<65 mA
Connection	M8 connector + cm 300 cable
Casing	Green anod.alum.
Dimension	14x95 mm
Linelength	Max 1,5mt
Protection class	IP64
Laser class	2M
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +140 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Dark red
Note	For better use you have to specify the focus distance. If not specified, emitter is focused for infinity. Line lenses with spread 5°, 20°, 30°, 45°, 90° available. The line has a wide, at a distance of mm 1000 from the emission point and perpendicularly to laser beam, as it follows: 05° spread = mm 70; 20° spread = mm 310; 30° spread = mm 660; 45° spread =

projections available on request

800 mm;  $90^{\circ}$  spread = mm 1800. You have to specify the spread that you wish. If not specified, emitter is shipped with a  $90^{\circ}$  spread lens. The visibility and the length of the line depend on the mounting of the laser and the brightness of the environment. Other optical

## **RELATED ACCESSORIES**

- Stabilized power supplier input 85-265Vac, output 5Vdc, 600mA, schuco plug
- Stabilized power supplier, input 8-30Vac-Vdc, output 5Vdc, 1A DIN attachment
- Stabilized power supplier input 100-240Vdc, output 5Vdc, 3A, DIN attachment
- Reclining bracket for 14 mm diam module, black
- Ball-shaped head bracket for 14 mm diam module, black
- Reduction bush for 14 mm diam module, black

