

Battery powered point, cross, line, circle emitter - Series LT2B20



N6505EXV00

Type of projection: Dot
Wavelength: 650 nm (red)
Max output power: 5 mW
Supply voltage: Batteria 1,5 Vdc tipo AA
Protection class: IP64

TECHNICAL DETAILS

| | |
|------------------------------------|---|
| Code | N6505EXV00 |
| Light source | Laser diode |
| Type of projection | Dot |
| Wavelength | 650 nm (red) |
| Max output power | 5 mW |
| Supply voltage | Batteria 1,5 Vdc tipo AA |
| Operating current | <130 mA |
| Connection | Cableless |
| Casing | Green anod.alum. |
| Dimension | 20x190 mm |
| Protection class | IP64 |
| Laser class | 3R |
| Storage temperature °C/°F | -40 +85 °C / -40 +185 °F |
| Operating temperature °C/°F | -10 +50 °C / 14 +140 °F |
| Application sector | Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc. |
| Color | Red |
| Note | Operating time for a battery: approx 8 hours. For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. Other optical projections available on request |

RELATED ACCESSORIES

- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —