

Battery powered point, cross, line, circle emitter - Series LT2B20



N6701EXVC0

Type of projection: Circle
Wavelength: 670 nm (dark red)
Max output power: 1 mW
Supply voltage: Batteria 1,5 Vdc tipo AA
Protection class: IP64

TECHNICAL DETAILS

Code	N6701EXVC0
Light source	Laser diode
Type of projection	Circle
Wavelength	670 nm (dark red)
Max output power	1 mW
Supply voltage	Batteria 1,5 Vdc tipo AA
Operating current	<130 mA
Connection	Cableless
Casing	Green anod.alum.
Dimension	20x190 mm
Protection class	IP64
Laser class	2
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +140 °F
Application sector	Nautical constructions, construction, rubber, plastic, metals, textiles, ceramics, wood, marble and stone, glass, paper, leather/skins, tyres, medicine, measurements etc.
Color	Dark red
Note	Operating time for a battery: approx 8 hours. For better use you have to specify the focus distance. If not specified, emitter is focused for mm 2000. The circle (spread 3°) has a central dot and a diameter of mm 40 at a distance of mm 1000 from the emission point. Circle lenses with spread 3°, 4°, 34°, 45° available. Other optical projections available on request

RELATED ACCESSORIES

- Reclining bracket for 20 mm diam module, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 20 mm diam module, black anod. alum., mountable on 20 mm diam rod
- Adjustable bracket for 20 mm diam module, flat, black, 12 mm diam inox rod included
- Protection for 20 mm diam module - white

LASERTECH®

— industrial laser pointers —