

Robust, powerful marker with bright green light - Series LT2V50



N7V30C8VL0

Type of projection: Line
Wavelength: 520 nm (bright green)
Max output power: 30 mW
Supply voltage: 80-265 Vac
Protection class: IP67

TECHNICAL DETAILS

Code	N7V30C8VL0
Light source	Laser diode
Type of projection	Line
Wavelength	520 nm (bright green)
Max output power	30 mW
Supply voltage	80-265 Vac
Operating current	<300 mA
Connection	Cable 3x0,75 cm 300 with schuco plug
Casing	Green anod.alum.
Dimension	50X220 mm
Linelength	Max 12mt
Protection class	IP67
Laser class	2M
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-20 +60 °C / -4 +140 °F
Application sector	Construction, metals, textiles, wood, marble and stones, leather/skins, rubber, metals, plastic, paper etc..
Color	Bright green
Note	The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment.Other optical projections available on request

RELATED ACCESSORIES

- Dimming flap 50 mm diam, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 50 mm diam module, black anod. alum., mountable on 20mm diam rod
- Protection for 50 mm diam module - white

LASERTECH®

— industrial laser pointers —