

Robust, powerful marker with bright green light - Series LT2V50



N7V30L4VL0

Type of projection: Line

Wavelength: 520 nm (bright green)

Max output power: 30 mW

Supply voltage: 9-36 Vdc 10-30 Vac Trigger 5-30Vdc

Protection class: IP67

TECHNICAL DETAILS

| | |
|------------------------------------|---|
| Code | N7V30L4VL0 |
| Light source | Laser diode |
| Type of projection | Line |
| Wavelength | 520 nm (bright green) |
| Max output power | 30 mW |
| Supply voltage | 9-36 Vdc 10-30 Vac Trigger 5-30Vdc |
| Operating current | <150 mA |
| Connection | M12 connector + cm 500 cable |
| Casing | Green anod.alum. |
| Dimension | 50X230 mm |
| Linelength | Max 12mt |
| Protection class | IP67 |
| Laser class | 2M |
| Storage temperature °C/°F | -40 +85 °C / -40 +185 °F |
| Operating temperature °C/°F | -20 +60 °C / -4 +140 °F |
| Application sector | Construction, metals, textiles, wood, marble and stones, leather/skins, rubber, metals, plastic, paper etc.. |
| Color | Bright green |
| Note | The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment.Other optical projections available on request |

RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Dimming flap 50 mm diam, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 50 mm diam module, black anod. alum., mountable on 20mm diam rod
- Protection for 50 mm diam module - white

LASERTECH®

— industrial laser pointers —