

Robust, powerful marker with bright green light - Series LT2V50



N7V80C8VL9

Type of projection: Perpendicular line exit

Wavelength: 520 nm (bright green)

Max output power: 80 mW

Supply voltage: 80-265 Vac

Protection class: IP64

TECHNICAL DETAILS

| | |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code | N7V80C8VL9 |
| Light source | Laser diode |
| Type of projection | Perpendicular line exit |
| Wavelength | 520 nm (bright green) |
| Max output power | 80 mW |
| Supply voltage | 80-265 Vac |
| Operating current | <300 mA |
| Connection | Cable 3x0,75 cm 300 with schuco plug |
| Casing | Green anod.alum. |
| Dimension | 50X250 mm |
| Linelength | Max 20mt |
| Protection class | IP64 |
| Laser class | 3B |
| Storage temperature °C/°F | -40 +85 °C / -40 +185 °F |
| Operating temperature °C/°F | -20 +60 °C / -4 +140 °F |
| Application sector | Construction, metals, textiles, wood, marble and stones, leather/skins, rubber, metals, plastic, paper etc.. |
| Color | Bright green |
| Note | The line generated by the laser beam lies on a plane which is perpendicular to the emitter device (90° angle as to the axis). The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment.Other optical projections available on request |

RELATED ACCESSORIES

- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 50 mm diam module, black anod. alum., mountable on 20mm diam rod
- Protection for 50 mm diam module - white

LASERTECH®

— industrial laser pointers —