

Classic powerful marker with red light - Series SCHREINER/S



SS305B4VL0

Type of projection: Line

Wavelength: 635 nm (bright red)

Max output power: 5 mW

Supply voltage: 9-36 Vdc 10-30 Vac

Protection class: IP67

TECHNICAL DETAILS

Code	SS305B4VL0
Light source	Laser diode
Type of projection	Line
Wavelength	635 nm (bright red)
Max output power	5 mW
Supply voltage	9-36 Vdc 10-30 Vac
Operating current	<30 mA
Connection	M12 connector + cm 500 cable
Casing	Green anod.alum.
Dimension	50X230 mm
Linelength	Max 2,5mt
Protection class	IP67
Laser class	2M
Storage temperature °C/°F	-40 +85 °C / -40 +185 °F
Operating temperature °C/°F	-10 +50 °C / 14 +122 °F
Application sector	Construction, metals, textiles, wood, marble and stones, leather/skins, rubber, metals, plastic, paper etc..
Color	Bright red
Note	The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment.Other optical projections available on request

RELATED ACCESSORIES

- Stabilized power supplier input 100-240Vac, output 24Vdc, 1,25A, 2 poles 10A plug
- Stabilized power supplier input 100-240Vdc, output 24Vdc, 1A, DIN attachment
- Dimming flap 50 mm diam, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 50 mm diam module, black anod. alum., mountable on 20mm diam rod
- Protection for 50 mm diam module - white

LASERTECH®

— industrial laser pointers —