

Classic powerful marker with red light - Series SCHREINER/S



SS310C8VL0

Type of projection: Line
Wavelength: 635 nm (bright red)
Max output power: 10 mW
Supply voltage: 80-265 Vac
Protection class: IP67

TECHNICAL DETAILS

| | |
|------------------------------------|---|
| Code | SS310C8VL0 |
| Light source | Laser diode |
| Type of projection | Line |
| Wavelength | 635 nm (bright red) |
| Max output power | 10 mW |
| Supply voltage | 80-265 Vac |
| Operating current | <900 mA |
| Connection | Cable 3x0,75 cm 300 with schuco plug |
| Casing | Green anod.alum. |
| Dimension | 50X220 mm |
| Linelength | Max 5mt |
| Protection class | IP67 |
| Laser class | 2M |
| Storage temperature °C/°F | -40 +85 °C / -40 +185 °F |
| Operating temperature °C/°F | -10 +50 °C / 14 +122 °F |
| Application sector | Construction, metals, textiles, wood, marble and stones, leather/skins, rubber, metals, plastic, paper etc.. |
| Color | Bright red |
| Note | The visibility and the lenght of the line depend on the mounting of the laser and the brightness of the enviroment.Other optical projections available on request |

RELATED ACCESSORIES

- Dimming flap 50 mm diam, black
- Inox rod diam mm 20x295, side milled, fixing holes (to be used with brackets 9SM2001N00 - 9SM5001N00)
- Horiz/vert twistable bracket for 50 mm diam module, black anod. alum., mountable on 20mm diam rod
- Protection for 50 mm diam module - white

LASERTECH®

— industrial laser pointers —